



Technical data

- 1.Nominal voltage: 300V/15A (IEC 250V/12A)  
PITCH:5.08mm
- 2.Insulation Withstands Voltage:  
AC 1600V/MIN / AC2500V/MIN
- 3.Insulation Resistance:  
1000M $\Omega$  or more at DC500V
- 4.Using temperature range:-40℃ ~115℃
- 5.Soldering temperature range:250℃ $\pm$ 10℃/5sec
- 6.Safety approval:
- 7.RoHS Compliance
- 8.Critical dimension:
- 9.Undimentioned Tolerances:

Dim.L=P $\times$ 5.08 Dim.B=(P-1) $\times$ 5.08 P = number of poles 2-24P	Dim B	Dim L
0-30mm	$\pm$ 0.15	$\pm$ 0.20
over 30mm-60mm	$\pm$ 0.20	$\pm$ 0.25
over 60mm-90mm	$\pm$ 0.25	$\pm$ 0.30
over 90mm	$\pm$ 0.30	$\pm$ 0.40

HAAH508 xx X xxx

- ① Poles 02-24
- ② Color
- ③ 0 Black 3 Orange 5 Green 6 Blue.....
- ④ Custom
- 000 K MARK 00K KUNACON MARK.....

2	PIN	BRASS	TIN PLATED	P				
1	BODY	PA66 UL94V-0		1				
MATERIAL								
DWG	WF: Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance
CHK:	WF: Zhang	DATE	2016.03.10	SCALE:	NONE 3:1 (.)	REV:	A	
APP:	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-AH508 Series Open type Right-Angle (90D)			
PART NO.	HAAH508xxxxxx			PART NO.	HAAH508-B002			
DWG NO.	HAA-A508-B002							

SIGN	DESCRIPTION	CHK	DATE



KUNA CONTACT TECHNOLOGY CO., LTD  
http://www.kunacon.com