



Technical data

- 1.Nominal voltage: 300V/15A
PITCH:7.62mm
2. Insulation Withstands Voltage:
AC 1600V/MIN
3. Insulation Resistace:
1000M Ω or more at DC500V
4. Using temperature range: -40C° ~ 115C°
5. Soldering temperature range: 250C° \pm 10C°/5sec

6. Safety approval:

7. RoHS Compliance

8. Critical dimension:

9. Undimentioned Tolerances:

Dim.L=(P-1)x7.62+5.82	Dim B	Dim L
Dim.B=(P-1)x7.62	0-30mm	± 0.15
P = number of poles 2-16P	over 30mm-60mm	± 0.20
	over 60mm-90mm	± 0.25
	over 90mm	± 0.30
		± 0.40

HAAH762 XX X XXX

- ① Poles 02-16
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue G Pale gray....
- ③ Custom
- 000 K MARK 00K KUNACON MARK.....

2	PIN	COPPER	TIN PLATED	P					
1	BODY	PA66 UL94V-0	ALL COLOR	1					
MATERIAL									
DWG	WF: Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	NOTES	Tolerance
CHK.	WF: Zhang	DATE	2016.03.10	SCALE:	NONE 4:1 (:)	REV.:	A		± 0.50
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-AH762 Series Open type Right-angle (90D)				
PART NO.		HAAH762xxxxxx			PART NO.		HAA-A762-B002		
DWG NO.		HAA-A762-B002			DWG NO.		HAA-A762-B002		

△
SIGN

DESCRIPTION

CHK.

DATE



KUNA Contact Technology Co., Ltd
http://www.kunacon.com

PART NO. HAAH762xxxxxx

