



Technical data

- 1.Nominal voltage: 300V/15A (IEC 250V/12A)
PITCH:5.08mm
- 2.Insulation Withstands Voltage:
AC 1600V/MIN / AC2500V/MIN
- 3.Insulation Resistance:
1000M Ω or more at DC500V
- 4.Using temperature range:-40C $^{\circ}$ ~115C $^{\circ}$
- 5.Soldering temperature range:250C $^{\circ}$ ±10C $^{\circ}$ /5sec

6.Safety approval:

7.RoHS Compliance

8.Critical dimension:

9.Undimensioned Tolerances:

Dim L=P×5.08	Dim B=(P-1)×5.08	Dim L	Dim B
P= number of poles 2-24P		±0.20	±0.20
0-30mm	±0.15	±0.25	±0.30
over 30mm-60mm	±0.20	±0.30	±0.40
over 60mm-90mm	±0.25	±0.30	±0.40
over 90mm	±0.30	±0.40	±0.40

HAAV508 XX X XXX

① Poles 02-24

② Color

0 Black 3 Orange 5 Green 6 Blue.....

③ Custom

000 K MARK 00K KUNACON MARK.....

2	PIN	BRASS	TIN PLATED	P					
1	BODY	PA66 UL94V-0		1					
ITEM NAME OF PART MATERIAL NOTES									
DWG	WF: Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance	±0.50
CHK:	WF: Zhang	DATE	2016.03.10	SCALE:	NONE 3:1 (.)	REV:	A		±0.30
APP:	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-AV508 Series Open type Vertical (180D)				
PART NO.		HAAV508XXXXXX			PART NO. HAAV508XXXXXX				
DWG NO.		HAA-508-B001			DWG NO. HAA-508-B001				

△	SIGN	DESCRIPTION	CHK.	DATE

