

Technical data
 1.Nominal voltage: 300V/8A (IEC 160V/8A)
 PITCH:3.5mm

2.Insulation Withstands Voltage:
 AC1600V/MIN / AC 2500V/MIN

3.Insulation Resistace:
 1000M Ω or more at DC500V

4.Using temperature range:-40 $^{\circ}$ C ~115 $^{\circ}$ C

5.Soldering temperature range:250 $^{\circ}$ C \pm 10 $^{\circ}$ C/5sec

6.Safety approval:

7.RoHS Compliance

8.Critical dimension:

9.Undimensioned Tolerances:

Dim L=(P-1)x3.5+4.9	Dim B	Dim L
Dim B=(P-1)x3.5	±0.15	±0.20
P= number of poles	±0.20	±0.25
0-30mm	±0.25	±0.30
over 30mm-60mm	±0.30	±0.40
over 60mm-90mm		
over 90mm		

HABH350 xxx x xxx

① Poles 02-24


② Color

③ Black 3 Orange 5 Green 6 Blue.....

④ Custom

000 K MARK 00K KUNACON MARK.....

2	PIN	BRASS	TIN PLATED	P					
1	BODY	PA66 UL94V-0		1					
MATERIAL									
DWG	WF. Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance	±0.50
CHK.	WF. Zhang	DATE	2016.03.10	SCALE:	NONE 4:1 (:)	REV.:	A	Tolerance	±0.30
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-BH350 Series Close type Right-angle(90D)			Tolerance	±0.10
PART NO.		HABH350xxxxxxx			PART NO.		HA-B350-B002		
DWG NO.		HA-B350-B002			DWG NO.		HA-B350-B002		
SIGN					DESCRIPTION				
CHK.					DATE				



KUNA Contact Technology Co., Ltd

http://www.kunacon.com