



Technical data

- 1.Nominal voltage: 300V/8A (IEC 160V/8A)  
PITCH:3.81mm
- 2.Insulation Withstands Voltage:  
AC1600V/MIN / AC 2500V/MIN
- 3.Insulation Resistace:  
1000MΩ or more at DC500V
- 4.Using temperature range:-40°C ~115°C
- 5.Soldering temperature range:250°C±10°C/5sec
- 6.Safety approval:
- 7.RoHS Compliance
- 8.Critical dimension:
- 9.Undimensioned Tolerances:

Dim L=(P-1)x3.81+5.0	Dim B	Dim L
Dim B=(P-1)x3.81	±0.15	±0.20
P= number of poles	±0.20	±0.25
0-30mm	±0.25	±0.30
over 30mm-60mm	±0.30	±0.40
over 60mm-90mm		
over 90mm		

HABH381 xxx x xxx

- ① Poles 02-24
- ② Color
- ③ Black 3 Orange 5 Green 6 Blue.....
- ④ Custom
- 000 K MARK 00K KUNACON MARK.....

2	PIN	BRASS	TIN PLATED	P					
1	BODY	PA66 UL94V-0		1					
MATERIAL									
DWG	WF. Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance	±0.50
CHK.	WF. Zhang	DATE	2016.03.10	SCALE:	NONE 4:1 ( : )	REV.:	A	Tolerance	±0.30
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-BH381 Series Close type			Tolerance	±0.10
				PART NO.	HABH381xxxxxx				±1°
				DWG NO.	HA-B381-B002				
SIGN					DESCRIPTION				
CHK.					DATE				
					KUNA Contact Technology Co., Ltd <a href="http://www.kunacon.com">http://www.kunacon.com</a>				