



Technical data

- 1.Nominal voltage: 300V/15A (IEC 320V/12A) PITCH:5.08mm
- 2.Insulation Withstands Voltage: AC 1600V/MIN / AC 2500V/MIN
- 3.Insulation Resistace: 1000MΩ or more at DC500V
- 4.Using temperature range:-40°C ~115°C
- 5.Soldering temperature range:250°C±10°C/5sec
- 6.Safety approval:
- 7.RoHS Compliance
- 8.Critical dimension:
- 9.Undimensioned Tolerances:

Dim.L=P×5.08±2.0	Dim B	Dim L
Dim.B=(P-1)×5.08	0-30mm	±0.15
P = number of poles 2-24P	over 30mm-60mm	±0.20
	over 60mm-90mm	±0.25
	over 90mm	±0.30
		±0.40

- HABV508 XX X XXX
- ① Poles 02-24
 - ② Color
 - 0 Black 3 Orange 5 Green 6 Blue.....
 - ③ Custom
 - 000 K MARK 00K KUNACON MARK.....

ITEM	NAME OF PART	MATERIAL	NOTES	QTY
1	BODY	COPPER	TIN PLATED	P
2	PIN			
DWG. WF. Zhang DATE 2016.03.10 UNITS: MM SHEET: 1 OF 1 Tolerance ±0.50				
CHK. WF. Zhang DATE 2016.03.10 SCALE: NONE 3:1 (.) REV.: A ±0.30				
APP. Marlin Zhang DATE 2016.03.31 TITLE: HA-BV508 Series Close type XXX ±0.10				
PART NO. HABV508XXXXXX X°				
DWG NO. HA-B508-B001				

△	SIGN	DESCRIPTION	CHK.	DATE

KUNA Contact Technology Co., Ltd
http://www.kunacon.com