



Technical data

1. Nominal voltage: 300V/15A (IEC 250V/12A)  
PITCH: 5.08mm
2. Insulation Withstands Voltage:  
AC 1600V/MIN / AC 2500V/MIN
3. Insulation Resistance:  
1000M $\Omega$  or more at DC500V
4. Using temperature range: -40°C ~ 115°C
5. Soldering temperature range: 250°C  $\pm$  10°C / 5sec
6. Safety approval:
7. RoHS Compliance
8. Critical dimension:
9. Undimensioned Tolerances:

Dim L = (P + 2) x 5.08	Dim B	Dim L
Dim B = P - 1 x 5.08	P = number of poles	
0-30mm	$\pm 0.15$	$\pm 0.20$
over 30mm-60mm	$\pm 0.20$	$\pm 0.25$
over 60mm-90mm	$\pm 0.25$	$\pm 0.30$
over 90mm	$\pm 0.30$	$\pm 0.40$

- HACH508 xx x xxx
- ① Poles 02-24
  - ② Color: 0 Black 3 Orange 5 Green 6 Blue.....
  - ③ Custom 000 K MARK 00K KUNACON MARK.....

3	FLANGE NUT	BRASS	TIN PLATED	2
2	PIN	COPPER		P
1	BODY	PA66 UL94V-0		1

  

ITEM NAME OF PART		MATERIAL		NOTES	
DWG	WF. Zhang	DATE	2016.03.10	UNITS	MM
CHK.	WF. Zhang	DATE	2016.03.10	SCALE	NONE 3:1 ( : )
APP.	Marvin Zhang	DATE	2016.03.31	TITLE	HA-CH508 Series W/Flange type Right-Angle (90D)
PART NO.	HACH508xxxxxx	PART NO.	HA-C508-B002	DWG NO.	HA-C508-B002

  

APPROVAL	SIGNATURE	DATE	TOLERANCE
			$\pm 0.50$
			$\pm 0.30$
			$\pm 0.10$
			$\pm 1^{\circ}$

DESCRIPTION	CHK.	DATE

SIGNATURE	DATE