



Technical data

- 1.Nominal voltage: 300V/15A
PITCH:7.62mm
- 2.Insulation Withstands Voltage:
AC 1600V/MIN
- 3.Insulation Resistace:
1000MΩ or more at DC500V
- 4.Using temperature range:-40C° ~115C°
- 5.Soldering temperature range:250C°±10C°/5sec
- 6.Safety approval:
- 7.RoHS Compliance
- 8.Critical dimension:
- 9.Undimensioned Tolerances:

Dim.L=(P-1)x7.62+18.2	Dim B	Dim L
Dim.B=(P-1)x7.62	±0.15	±0.20
P = number of poles 2-16P	over 30mm-60mm	±0.25
	over 60mm-90mm	±0.30
	over 90mm	±0.40

HABV762 XX X XXX

- ① Poles 02-16
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue G Pale gray....
- ③ Custom
- 000 K MARK 00K KUNACON MARK.....

3	FLANGE NUT	BRASS	TIN PLATED	P	2
2	PIN	COPPER	ALL COLOR	P	1
1	BODY	PA66 UL94V-0			
ITEM NAME OF PART MATERIAL NOTES					
DWG	W/F: Zhang	DATE 2016.03.10	UNITS: MM	SHEET: 1 OF 1	Tolerance
CHK.	W/F: Zhang	DATE 2016.03.10	SCALE: NONE 3:1 (.)	REV.: A	±0.50
APP.	Marvin Zhang	DATE 2016.03.31	TITLE: HA-CV762 Series W/F type		±0.30
			Vertical (180D)		±0.10
			PART NO. HACV762xxxxxx		±1°
			DWG NO. HA-C762-B001		

△	SIGN	DESCRIPTION	CHK.	DATE
---	------	-------------	------	------

	KUNA Contact Technology Co., Ltd		
	http://www.kunacon.com		