



Technical data

- 1.Nominal voltage: 300V/8A
PITCH:3.81mm
- 2.Insulation Withstands Voltage:
AC 1600V/MIN
- 3.Insulation Resistance:
1000M Ω or more at DC500V
- 4.Using temperature range:-40C° ~115C°
- 5.Soldering temperature range:250C° \pm 10C°/5sec
- 6.Safety approval:
- 7.RoHS Compliance
- 8.Critical dimension:
- 9.Undimensioned Tolerances:

	Dim B	Dim L
0-30mm	± 0.15	± 0.20
over 30mm-60mm	± 0.20	± 0.25
over 60mm-90mm	± 0.25	± 0.30
over 90mm	± 0.30	± 0.40

HAEH381 XX X XXX

- ① Poles 04-4(2*2p-2*24p)
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue:....
- ③ Custom
- 000 K MARK 00K KUNACON MARK

ITEM	NAME OF PART	MATERIAL	NOTES
4	Short PIN	BRASS	TIN PLATED
3	Long PIN	BRASS	TIN PLATED
2	COVER	PA66 UL94V-0	
1	BODY	PA66 UL94V-0	

DWG	WF. Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance
CHK.	WF. Zhang	DATE	2016.03.10	SCALE:	NONE 3:1 (.)	REV.:	A	± 0.50
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-EH381 Series Close type X.X			± 0.30
					Right-Angle (90D)			± 0.10

SIGN	DESCRIPTION	CHK.	DATE

KUNA Contact Technology Co., Ltd
http://www.kunacon.com

PART NO. HAEH381xxxxxx
DWG NO. HA-E381-B001