



Technical data

- 1.Nominal voltage: 300V/15A
PITCH:5.08mm
- 2.Insulation Withstands Voltage:
AC 1600V/MIN
- 3.Insulation Resistace:
1000MΩ or more at DC500V
- 4.Using temperature range:-40℃ ~ 115℃
- 5.Soldering temperature range:250℃±10℃/5sec
- 6.Safety approval:
- 7.RoHS Compliance
- 8.Critical dimension:
- 9.Undimensioned Tolerances:

Dim.L=1/2P×5.08±2.0	Dim B	Dim L
Dim.B=(1/2P-1)×5.08	0-30mm	±0.15
P = number of poles 4-48P	over 30mm-60mm	±0.20
	over 60mm-90mm	±0.25
	over 90mm	±0.30
		±0.40

HAEH508 XX X XXX

- ① Poles 04-48(2×2p-2×24p)
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue....
- ③ Custom
- 000 K MARK 00K KUNACON MARK

4	Short PIN	COPPER	TIN PLATED	1/2P
3	Long PIN	COPPER	TIN PLATED	1/2P
2	COVER	PA66 UL94V-0		1
1	BODY	PA66 UL94V-0		1

DWG	WF. Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance	±0.50
CHK.	WF. Zhang	DATE	2016.03.10	SCALE:	NONE 2:1 (.)	REV.:	A		±0.30
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-EH508 Series Close type X.X				±0.10
					Right-Angle (90D)				X.XX
									X°
									±1°

△	SIGN		
	DESCRIPTION		
	CHK.		
	DATE		

KUNA Contact Technology Co., Ltd
http://www.kunacon.com

PART NO. HA-EH508XXXXXX
DWG NO. HA-E508-B001