



Technical data

- 1.Nominal voltage: 150V/4A
- PITCH:2.5mm
- 2.Insulation Withstands Voltage: AC1300V/MIN
- 3.Insulation Resistace: 1000MΩ or more at DC500V
- 4.Using temperature range:-40C° ~115C°
- 5.Soldering temperature range:250C°±10C°/5sec

- 6.Safety approval:
- 7.RoHS Compliance
- 8.Critical dimension:
- 9.Undimensioned Tolerances:

Dim L=(P-1)X2.5+4.4	Dim B	Dim L
Dim B=(P-1)X2.5	0-30mm	±0.15
P = 1/2 number of poles(04-48)	over 30mm-60mm	±0.20
	over 60mm-90mm	±0.25
	over 90mm	±0.30
		±0.40

- HAEV250 xx x xxx
- ① Poles 04-48 (2x2P-2x24P)
 - ② Color
 - 0 Black 3 Orange 5 Green 6 Blue G Pale grey....
 - ③ Custom
 - 000 K MARK 00K KUNACON MARK.....

3	PIN	Copper	TIN PLATED	P
2	COVER	PA66 UL 94V-0	ALL COLOR	1
1	BODY	PA66 UL 94V-0	ALL COLOR	1
ITEM NAME OF PART				
MATERIAL				
DWG. W/F. Zhang	DATE 2016.03.10	UNITS: MM	SHEET: 1 OF 1	Tolerance
CHK. W/F. Zhang	DATE 2016.03.10	SCALE: NONE 4:1 (:)	REV.: A	X
APP. Marvin Zhang	DATE 2016.03.31	TITLE: HA-EV250 Series Close type		X.X
		Vertical(180D)		X.XX
				±0.10
				X°
				±1°

Δ	SIGN	DESCRIPTION	CHK.	DATE
---	------	-------------	------	------

KUNA Contact Technology Co., Ltd
http://www.kunacon.com

PART NO.	HAEB250xxxxxx
DWG NO.	HA-E250-B002