



Technical data

- 1 Nominal voltage: 300V/8A
PITCH:3.81mm
- 2 Insulation Withstands Voltage:
AC 1600V/MIN
- 3 Insulation Resistance:
1000M Ω or more at DC500V
- 4 Using temperature range:-40C° ~ 115C°
- 5 Soldering temperature range:250C° \pm 10C°/5sec
- 6 Safety approval:
- 7 RoHS Compliance
- 8 Critical dimension:
- 9 Undimensioned Tolerances:

Dim L=(1/2P -1)x3.81+5.2	Dim B	Dim L
Dim B=(1/2P -1)x3.81	0-30mm	± 0.15
P = number of poles 4-4.8P	over 30mm-60mm	± 0.20
	over 60mm-90mm	± 0.25
	over 90mm	± 0.30
		± 0.40

HAEV381 xx x xxx

- ① Poles 04-48(2*2p-2*24p)
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue:....
- ③ Custom
- 000 K MARK 00K KUNACON MARK

3	PIN	BRASS	TIN PLATED	P
2	COVER	PA66 UL 94V-0		1
1	BODY	PA66 UL 94V-0		1
ITEM NAME OF PART MATERIAL NOTES				
DWG	WF. Zhang	DATE 2016.03.10	UNITS: MM	SHEET: 1 OF 1
CHK.	WF. Zhang	DATE 2016.03.10	SCALE: NONE 3:1 (.)	REV.: A
APP.	Marvin Zhang	DATE 2016.03.31	TITLE: HA-EV381 Series Close type XXX Vertical (180D)	Tolerance: X.XX ± 0.30 XXX ± 0.10 X* $\pm 1^{\circ}$
PART NO.	HAEV381xxxxxx		PART NO.	HA-E381-B002
DWG NO.	HA-E381-B002			

△	SIGN	DESCRIPTION	CHK.	DATE



KUNA Contact Technology Co., Ltd
http://www.kunacon.com