



Technical data

- 1.Nominal voltage: 300V/8A  
PITCH:3.81mm
- 2.Insulation Withstands Voltage:  
AC 1600V/MIN
- 3.Insulation Resistance:  
1000MΩ or more at DC500V
- 4.Using temperature range:-40℃ ~115℃
- 5.Soldering temperature range:250℃±10℃/5sec
- 6.Safety approval:
- 7.RoHS Compliance
- 8.Critical dimension:
- 9.Undimensioned Tolerances:

Dim.L=(1/2P-1)x3.81+16.2	Dim B	Dim L
Dim.B=(1/2P-1)x3.81	0-30mm	±0.15
P = number of poles 4-4.8P	over 30mm-60mm	±0.20
	over 60mm-90mm	±0.25
	over 90mm	±0.30
		±0.40

HAFH381 xx X xxx

- ① Poles 04-48(2x2p-2x24p)
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue:....
- ③ Custom
- 000 K MARK 00K KUNACON MARK

5	FLANGE NUT	BRASS			4
4	Short PIN	BRASS	TIN PLATED		1/2P
3	Long PIN	BRASS	TIN PLATED		1/2P
2	COVER	PA66 UL94V-0			1
1	BODY	PA66 UL94V-0			1

DWG	W/F: Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance	±0.50
CHK	W/F: Zhang	DATE	2016.03.10	SCALE:	NONE 3:1( : )	REV.:	A		±0.30
APP	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-FH381 Series W/F type				±0.10
					Right-Angle (90D)				±1°
				PART NO.	HAFH381xxxxxx				
				DWG NO.	HA-F381-B001				

△	SIGN		
	DESCRIPTION		
	CHK		
	DATE		



KUNA Contact Technology Co., Ltd  
http://www.kunacon.com