



Technical data

- 1.Nominal voltage: 150V/8A
PITCH:3.81mm
- 2.Insulation Withstands Voltage:
AC 1300V/MIN
- 3.Insulation Resistance:
1000MΩ or more at DC500V
- 6.Using temperature range:-40C~+115C°
- 7.Undimentioned Tolerances:

Dim L= P-1 X3.81+5.0	Dim B	Dim L
Dim B= P-1 X3.81	±0.15	±0.20
P=1/2 Number of poles (4~48P)	±0.20	±0.25
0~30mm	±0.25	±0.30
over 30mm~60mm	±0.30	±0.40
over 60mm~90mm		
over 90mm		

- 8.Safety approval:
- 9.RoHS Compliance
- 10.Critical dimension:
- HFBH381 xx x xxx
- ① Poles 0+~48(2x02~2x24)
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue G Pale Gray.....
- ③ Custom
- 000 K MARK 00K KUNACON MARK.....

3	PIN 2	COPPER	TIN PLATED	1/2P					
2	PIN 1	COPPER	TIN PLATED	1/2P					
1	BODY	PA66 UL94V-0	ALL COLOR	1					
ITEM NAME OF PART MATERIAL NOTES									
DWG.	WF.	Zhang	DATE	2016.03.10	MM	SHEET:	1 OF 1	Tolerance	
CHK.	WF.	Zhang	DATE	2016.03.10	SCALE:	NONE 2.5:1 (.)	REV.: A	X	
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HF-BH381 Series Close type X.X				
PART NO. HFBH381xxxxxx					Right angle (90D)				
PART NO. HFBH381xxxxxx					X.XX ±0.30				
PART NO. HFBH381xxxxxx					X° ±0.10				
DWG NO. HF-B381-B001					±1°				

△	SIGN	DESCRIPTION	CHK.	DATE
---	------	-------------	------	------

