



Technical data

- 1.Nominal voltage: 150V/8A
- PITCH:3.81mm
- 2.Insulation Withstands Voltage: AC 1600V/MIN
- 3.Insulation Resistance: 1000M Ω or more at DC500V
- 4.Using temperature range:-40C ~+115C
- 5.Undimentioned Tolerances:

0-30mm over 30mm-60mm over 60mm-90mm over 90mm	Dim B ± 0.15 ± 0.20 ± 0.25 ± 0.30	Dim L ± 0.20 ± 0.25 ± 0.30 ± 0.40
---	---	---

- 6.Safety approval:
- 7.RoHS Compliance
- 8.Critical dimension:
- HFVB381 xx X xxx
 - ① Poles 0/-4(12x02-2x24)
 - ② Color
 - 0 Black 3 Orange 5 Green 6 Blue G Pale Gray....
 - ③ Custom
 - 000 K MARK 00K KUNACON MARK....

2	PIN	COPPER	TIN PLATED	P					
1	BODY	PA66 UL94V-0	ALL COLOR	1					
MATERIAL									
DWG	WF. Zhang	DATE	2016.03.10	UNITS	MM	SHEET	1 OF 1	Tolerance	0.1TY
CHK.	WF. Zhang	DATE	2016.03.10	SCALE	NONE 2.5:1 (.)	REV.	A	X	± 0.50
APP.	Marvin Zhang	DATE	2016.03.31	TITLE	HF-BV381 Series Close type	X	X	X	± 0.30
					Vertical (180D)	X	X	X	± 0.10
						X	X	X	$\pm 1^{\circ}$
PART NO.		HFVB381xxxxxx			DWG NO.		HF-B381-B002		

△	SIGN	DESCRIPTION	CHK.	DATE
---	------	-------------	------	------

KUNA Contact Technology Co. Ltd
<http://www.kunacon.com>