

Technical data

- 1.Nominal voltage: 150V/8A
PITCH:3.81mm
 - 2.Insulation Withstands Voltage:
AC 1600V/MIN
 - 3.Insulation Resistace:
1000MΩ or more at DC500V
 - 4.Flange tightening torque:
3.0kgf.cm (0.3Nm)
 - 5.Flange screw thread: M2.5
 - 6.Using temperature range:-40C ~+115C°
 - 7.Undimensioned Tolerances:
- | | | |
|-----------------------|----------------|-------|
| Dim L=(P-1)X3.81+14.8 | Dim B | Dim L |
| Dim B=(P-1)X3.81 | ±0.15 | ±0.20 |
| P=1/2 Number of poles | over 30mm-60mm | ±0.20 |
| | over 60mm-90mm | ±0.25 |
| | over 90mm | ±0.30 |
| | | ±0.40 |
- 8.Safety approval:
 - 9.RoHS Compliance
 - 10.Critical dimension:


HFCH381 xx X xxx
 ① Poles 04-48(2*02-2*24)
 ② Color
 0 Black 3 Orange 5 Green 6 Blue G Pale Gray.....
 ③ Custom
 000 K MARK 00K KUNACON MARK.....

4	Screw nut	BRASS			4
3	PIN 2	COPPER	TIN PLATED		1/2P
2	PIN 1	COPPER	TIN PLATED		1/2P
1	BODY	PA66 UL94V-0	ALL COLOR		1

ITEM	NAME OF PART	MATERIAL	NOTES
DWG	WF-Zhang	DATE	2016.03.10
CHK	WF-Zhang	DATE	2016.03.10
APP	Marvin Zhang	DATE	2016.03.31
TITLE:	HF-CH381 Series W/Flange Right angle (90D)		
PART NO.:	HFCH381xxxxxxx		
DWG NO.:	HF-C381-B001		

SCALE:	NONE 2.5:1 (.)	REV.: A	SHEET:	1 OF 1	Tolerance
X	±0.50	X	±0.30	X	±0.10
X	±0.10	X	±1°		

△	SIGN	DESCRIPTION	CHK	DATE



KUNA Contact Technology Co. Ltd
<http://www.kunacon.com>