




Technical data

- 1.Nominal voltage: 150V/8A
PITCH:3.81mm
- 2.Insulation Withstands Voltage:
AC 1300V/MIN
- 3.Insulation Resistance:
1000M Ω or more at DC500V
- 4.Flange tightening torque:
3.0kgf.cm (0.3Nm)
- 5.Flange screw thread: M2.5
- 6.Using temperature range:-40C ~+115C $^{\circ}$
- 7.Undimensioned Tolerances:

0-30mm	Dim B	± 0.20	Dim L	± 0.25
over 30mm-60mm		± 0.20		± 0.30
over 60mm-90mm		± 0.25		± 0.30
over 90mm		± 0.30		± 0.40
- 8.Safety approval: 
- 9.RoHS Compliance 
- 10.Critical dimension: 

HFCV381 xxx x xxx
 ① Poles 04-48(2x02-2x24)
 ② Color
 0 Black 3 Orange 5 Green 6 Blue 6 Pale Gray.....
 ③ Custom
 000 K MARK 00K KUNACON MARK.....

3	Screw nut	BRASS			4
2	PIN	COPPER			P
1	BODY	PA66 UL94V-0			1
ITEM NAME OF PART MATERIAL NOTES					
DWG	WF-Zhang	DATE	2016.03.10	UNITS	MM
CHK	WF-Zhang	DATE	2016.03.10	SCALE	NONE 2.5:1 (.)
APP	Marvin Zhang	DATE	2016.03.31	TITLE	HFCV381 Series W/Flange Vertical (180D)
KUNA Contact Technology Co. Ltd		PART NO. HFCV381xxxxxx		Tolerance	
http://www.kunacon.com		DWG NO. HFC-381-B002		X: ± 0.50 X.X: ± 0.30 XXX: ± 0.10 X $^{\circ}$: $\pm 1^{\circ}$	
SIGN		DESCRIPTION		CHK	DATE