



Technical data

- 1. Nominal voltage: 150V/4A
- PITCH: 2.5mm
- 2. Connection capacity: AWG 28-20
- 3. Insulation Withstands Voltage: AC 1300V/MIN
- 4. Insulation Resistance: 1000M Ω or more at DC500V
- 5. Stripping length: 7-8mm
- 6. Using temperature range: -40C \pm 115C \circ
- 7. Undimentioned Tolerances:

0-30mm over 30mm-60mm over 60mm-90mm over 90mm	Dim B	Dim L
	± 0.15 ± 0.20 ± 0.25 ± 0.30	± 0.20 ± 0.25 ± 0.30 ± 0.40

8. Safety approval:

9. RoHS Compliance

10. Critical dimension:

PASD250 xxx x xxx

- ① Poles 02-24
- ② Color
- ③ Black 3 Orange 5 Green 6 Blue G Pale grey.....
- ④ Custom
- ⑤ 000 K MARK 00K KUNACON MARK.....

ITEM	NAME OF PART	MATERIAL	NOTES
5	SPRING	Stainless steel	P
4	CONTACT	BRONZE (PbZ)	P
3	LEVEL	PBT UL94V-0	P
2	COVER	PA66 UL94V-0	1
1	BODY	PA66 UL94V-0	1

DWG	WF	Zhang	DATE	2016.03.10	UNITS	MM	SHEET	1 OF 1	Tolerance
CHK	WF	Zhang	DATE	2016.03.30	SCALE	NONE 2.5:1 (.)	REV	A	X
APP	Marvin Zhang	DATE	2016.03.30	TITLE	PA-SD250 Series Without flange type				
PART NO.	PASD250xxxxxx								
DWG NO.	PAS-SD250-B001								

SIGN	DESCRIPTION	CHK	DATE

