



Technical data

- 1. Nominal voltage: 150V/8A
- PITCH: 3.5mm
- 2. Connection capacity: AWG 24-16
- 3. Insulation Withstands Voltage: AC 1300V/MIN
- 4. Insulation Resistance: 1000M Ω or more at DC500V
- 5. Stripping length: 9-10mm
- 6. Using temperature range: -40C \circ +115C \circ
- 7. Undimensioned Tolerances:

Dim L = (P-1)X3.5+4.2	Dim B	Dim L
Dim B = (P-1)X3.5	0-30mm	± 0.15
P = number of poles	over 30mm-60mm	± 0.20
	over 60mm-90mm	± 0.25
	over 90mm	± 0.30
		± 0.30
		± 0.40

- 8. Safety approval:
 - 9. RoHS Compliance
 - 10. Critical dimension:
- PBFD350 XX.X.XXX
 ① Poles 02-24
 ② Color
 0 Black 3 Orange 5 Green 6 Blue G Pale grey....
 ③ Custom
 000 K MARK 00K KUNACON MARK.....

ITEM	NAME OF PART	MATERIAL	NOTES
6	WIRE GUARD	Stainless steel	P
5	CONTACT	BRONZE (PbBz)	P
4	FLANGE	STEEL C1018	2
3	LEVEL	PBT UL94V-0	P
2	COVER	PA66 UL94V-0	1
1	BODY	PA66 UL94V-0	1

DWG	WF	Zhang	DATE	2016.03.10	UNITS	MM	SHEET	1 OF 1	Tolerance
CHK	WF	Zhang	DATE	2016.03.30	SCALE	NONE 3:1 (.)	REV	A	X
APP	Marvin Zhang	DATE	2016.03.30	TITLE	PB-FD350 Series with Screw X.X flange type X.XX X ⁺				
PART NO.	PBFD350XXXXXX								
DWG NO.	PB-F350-B001								

DATE	DESCRIPTION	CHK	SIGN

DATE	DESCRIPTION	CHK	SIGN

KUNA Contact Technology Co. Ltd
<http://www.kunacon.com>