



Technical data

- 1.Nominal voltage: 300V/16A  
PITCH:5.08mm
- 2.Connection capacity:  
AWG 26-14
3. Insulation Withstands Voltage:  
AC 1600V/MIN
4. Insulation Resistance:  
1000M $\Omega$  or more at DC500V
5. Tightening torque:  
4.0kgf.cm (0.4N.m)
6. Screw thread: M3
7. Stripping length: 6-7mm
8. Using temperature range: -40C° ~ 115C°  
Soldering temperature: 250 $\pm$ 10C°/5s
9. Undimen stoned Tolerances:

Dim L = P $\times$ 5.08 Dim B = (P-1) $\times$ 5.08 P = number of poles (2-24p)	Dim B	Dim L
0-30mm	$\pm 0.15$	$\pm 0.20$
over 30mm-60mm	$\pm 0.20$	$\pm 0.25$
over 60mm-90mm	$\pm 0.25$	$\pm 0.30$
over 90mm	$\pm 0.30$	$\pm 0.40$

10. Safety approval:
11. RoHS Compliance
12. Critical dimension:

DAHMS08 xx x xxx  
 ① Poles 02-24  
 ② Color  
 0 Black 3 Orange 5 Green 6 Blue 8 Grey....  
 ③ Custom  
 000 "K" logo 00K KUNACON logo

4	WIRE GUARD	Stainless steel			P
3	SCREW	STEEL	M3 $\times$ 0.5, Zn Plated		P
2	CAGE	BRASS	M3 $\times$ 0.5, Tin PLATED		P
1	BODY	PA66 UL94V-0	ALL COLOR		1

DWG	WF. Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance
CHK.	WF. Zhang	DATE	2016.03.31	SCALE:	NONE 3:1 (.)	REV.:	A	$\pm 0.50$
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	DA-H508 Series 1-Interlock			$\pm 0.30$
					stackable type			$\pm 0.10$
					stackable type			$\pm 0.10$
					stackable type			$\pm 0.10$
PART NO.	DAHMS08xxxxxx							
DWG NO.	DAH508-B001							

△	SIGN	DESCRIPTION	CHK.	DATE

KUNA CONTACT Technology Co. Ltd  
<http://www.kunacontact.com>