



Technical data

- 1.Nominal voltage: 300V/10A
- PITCH:3.5mm
- 2.Connection capacity:
AWG 26-16

- 3.Insulation Withstands Voltage:
AC 1600V/MIN

- 4.Insulation Resistace:
1000MΩ or more at DC500V

- 5.Tightening torque:
2.0kgf.cm (0.2N.m)

- 6.Screw thread: M2

- 7.Stripping length: 5-6mm

- 8.Using temperature range:-40C ~+15C°

- Soldering temperature:250±10C°/5s

- 9.Undimen stioned Tolerances:

Dim L=Px3.5	Dim B	Dim L
Dim B=(P-1)x3.5	±0.10	±0.15
P= number of poles(2-24P)	over 30mm-60mm	±0.15
	over 60mm-90mm	±0.20
	over 90mm	±0.25
		±0.30

- 10.Safety approval:
- 11.RoHS Compliance
- 12.Critical dimension:

DCHM350 XX X XXX
 ① Poles 02-24
 ② Color
 0 Black 3 Orange 5 Green 6 Blue.....
 ③ Custom
 000 "K" logo 00K KUNACON logo

4	WIRE GUARD	Stainless steel			P
3	SCREW	STEEL	M2.0, Zn Plated		P
2	CAGE	BRASS	M2.0, Tin PLATED		P
1	BODY	PA66 UL94V-0	ALL COLOR		1
MATERIAL NOTES					
DWG	WF. Zhang	DATE	2016.03.10	UNITS:	MM
CHK.	WF. Zhang	DATE	2016.03.31	SCALE:	NONE 3:1 (.)
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	DC-H350 Series "-" slot
PART NO. DCHM350xxxxxxx					
DWG NO. DC-H350-B001					
					Tolerance
					±0.50
					±0.30
					±0.10
					±1°

△	SIGN	CHK.	DATE
	DESCRIPTION		

KUNA Contact Technology Co, Ltd
<http://www.kunacon.com>