



Technical data
 1.Nominal voltage: 300V/15A (CQC 250V/24A)
 PITCH:5.0mm

2.Connection capacity:
 AWG 24-12 / 0.2-2.5mm²

3. Insulation Withstands Voltage:
 AC 1600V/MIN / AC 2500V/MIN

4. Insulation Resistance:
 1000M Ω or more at DC500V

5. Tightening torque:
 3.5kgf.cm (3.0lb-in/0.35N.m) / 0.4N.m

6. Screw thread: M2.6

7. Stripping length: 5-6mm

8. Using temperature range: -40 $^{\circ}$ C - 115 $^{\circ}$ C
 Soldering temperature: 250 \pm 10 $^{\circ}$ C / 5s

Dim.L=P \times 5.0 Dim.B=(P-1) \times 5.0 P= number of poles(2-24p)	Dim B	Dim L
0-30mm over 30mm-60mm over 60mm-90mm over 90mm	\pm 0.15 \pm 0.20 \pm 0.25 \pm 0.30	\pm 0.20 \pm 0.25 \pm 0.30 \pm 0.40

- 10. Safety approval: Pending
- 11. RoHS Compliance
- 12. Critical dimension

DJHM500 xx x Vxx
 ① Poles 02-24
 ② Color
 0 Black 5 Green 6 Blue 8 Pale grey.....
 ③ Custom
 V10 K MARK VIK KUNACON MARK.....

4	WIRE GUARD	Stainless steel			P
3	SCREW	STEEL	M2.6 \times 0.45, Zn Plated		P
2	CAGE	BRASS	M2.6 \times 0.45, Tin PLATED		P
1	BODY	PA66 UL94V-0	ALL COLOR		1

ITEM	NAME OF PART	MATERIAL	NOTES
DWG.	Kobe, Kang	DATE	2016.04.19
CHK.	WF. Chang	DATE	2016.09.19
APP.	WF. Chang	DATE	2016.09.19

KUNA Contact Technology Co. Ltd	http://www.kunacon.com
PART NO. DJHM500xxxVxx	DWG NO. DJH500-B101

TITLE:	DJ-H500-90D Series "+r" Slot Screw (Square hole)
SCALE:	NONE 1:1
UNITS:	MM
SHEET:	1 OF 1
Tolerance	\pm 0.50 \pm 0.30 \pm 0.10 \pm 1 $^{\circ}$

DESCRIPTION	CHK.	DATE
SIGN		