



P.C.B. LAYOUT

Technical data

- 1.Nominal voltage: 150V/6A
PITCH:2.54mm
- 2.Connection capacity:
AWG 30-18
3. Insulation Withstands Voltage:
AC 1300V/MIN
4. Insulation Resistance:
1000MΩ or more at DC500V
5. Tightening torque:
1.5kgf.cm (0.15N.m)
6. Screw thread: M1.6
7. Stripping length: 4-5mm
8. Using temperature range: -40C ~+115C°
Soldering temperature: 250±10C°/5s

9.Undimen stoned Tolerances:

Dim L=P*2.54+0.4	Dim B	Dim L
Dim B=(P-1)*2.54	±0.15	±0.20
P= number of poles	±0.20	±0.25
0-30mm	±0.25	±0.30
over 30mm-60mm		
over 60mm-90mm		

10.Safety approval:

11.RoHS Compliance

12.Critical dimension:

EAHS254 xx x xxx

- ① Color
- ② Poles 02-24
- ③ Custom

0 Black 3 Orange 5 Green 6 Blue 8 Gray....
000 K MARK 00K KUNACON MARK

4	CONTACT	BRASS	Tin PLATED	P
3	SCREW	STEEL	M1.6*0.35, Zn Plated	P
2	CAGE	BRASS	M1.6*0.35, Ni PLATED	P
1	BODY	PA66 UL94V-0	ALL COLOR	1

ITEM	NAME OF PART	MATERIAL	NOTES
DWG W/F:	Zhang	DATE	2016.03.10
CHK:	W/F: Zhang	DATE	2016.03.31
APP:	Marvin Zhang	DATE	2016.03.31
TITLE:	EA-HS254 Series " " Slot		
PART NO.:	EAHS254xxxxxx		
DWG NO.:	EA-H254-B001		

UNITS:	MM	SHEET:	1 OF 1	Tolerance
SCALE:	NONE 5:1 (.)	REV.:	A	±0.50
				±0.30
				±0.10
				±1°

DESCRIPTION

CHK:

DATE

KUNUA Contact Technology Co, Ltd
http://www.kunuacon.com

EA-H254-B001