



Technical data

- 1. Nominal voltage: 300V/8A
- PITCH: 3.5mm
- 2. Insulation Withstands Voltage: AC 1600V/MIN

- 3. Insulation Resistance: 1000M $\Omega$  or more at DC500V
- 4. Using temperature range: -40C $^{\circ}$ -115C $^{\circ}$
- Soldering temperature: 260 $\pm$ 5C $^{\circ}$ /10s
- 5. Undimentioned Tolerances:

Dim L=(P-1) $\times$ 3.5+10.5	Dim B	Dim L
Dim B=(P-1) $\times$ 3.5	±0.15	±0.20
P=1/2 Number of poles (04-48P)	±0.20	±0.25
	±0.25	±0.30
	±0.30	±0.40
	±0.30	±0.40

- 6. Safety approval:
- 7. RoHS Compliance
- 8. Critical dimension:
- HGCV350 xxx x xxx
- ① Poles 04-48(2 $\times$ 02-2 $\times$ 24)
- ② Color
- ③ 0 Black
- ④ Custom
- 000 K MARK 00K KUNACON MARK

3	FLANGE NUT	BRASS	TIN PLATED	P	2
2	PIN	COPPER	BLACK	P	1
1	BODY	LCP UL94V-0	BLACK	P	1

  

ITEM	NAME OF PART	MATERIAL	NOTES
DWG.	WF. Zhang	DATE	2017.12.12
CHK.	WF. Zhang	DATE	2018.05.31
APP.		DATE	

  

TITLE:	HG-CV350 Series W/F type	X.X	±0.50
	Vertical (180D) THR	X.XX	±0.30
		X.XX	±0.10
		X <sup>*</sup>	±1 <sup>o</sup>

DESCRIPTION	DATE	CHK.	SIGN

KUNA Contact Technology Co., Ltd  
http://www.kunacon.com