



Technical data

- 1.Nominal voltage: 300V/8A
PITCH:3.5mm
- 2.Connection capacity:
AWG 24-16
- 3.Insulation Withstands Voltage:
AC 1600V/MIN
- 4.Insulation Resistance:
1000MΩ or more at DC500V
- 5.Stripping length: 9-10mm
- 6.Using temperature range:-40C ~+15C
- 7.Undimensioned Tolerances:

Dim L=(P-1)X3.5+4.2		Dim B	Dim L
Dim B=(P-1)X3.5		±0.15	±0.20
P = 1/2 Number of poles(0~4/8)		over 30mm-60mm	±0.25
		over 60mm-90mm	±0.30
		over 90mm	±0.40

- 8.Safety approval:
- 9.RoHS Compliance
- 10.Critical dimension: ∇
- PDFD350 XX X XXX
- ① Poles 2x2P-2x24P
- ② Color
- 0 Black 5 Green 6 Blue G Plae grey.....
- ③ Custom
- 000 K MARK 00K KUNACON MARK

6	FLANGE SCREW	STEEL	Zn PLATED	2
5	WIRE GUARD	Stainless steel		P
4	CONTACT	BRONZE (PbBi)	TIN PLATED	P
3	LEVEL	PBT UL94V-0	ORANGE	P
2	COVER	PA66 UL94V-0	ALL COLOR	1
1	BODY	PA66 UL94V-0	ALL COLOR	1

DWG. WF. Zhang		DATE	2017.12.13	UNITS:	MM	SHEET:	1 OF 1	Tolerance
CHK. WF. Zhang		DATE	2018.06.05	SCALE:	NONE 3:1 (.)	REV.:	A	±0.50
APP.:		DATE		TITLE:	PD-FD350 Series Double row			±0.30
					Plug With Flange			±0.10
					PDFD350XXXXXX			±1 ^o

SIGN	DESCRIPTION	CHK.	DATE

PART NO.	PD-F350-B001
DWG NO.	PD-F350-B001

KUNA Contact Technology Co. Ltd
http://www.kunacon.com