



Technical data

- 1.Nominal voltage: 300V/8A (IEC 160V/8A)
PITCH:3.81mm
- 2.Insulation Withstands Voltage:
AC1600V/MIN / AC 2500V/MIN
- 3.Insulation Resistance:
1000MΩ or more at DC500V
- 4.Using temperature range:-40C° ~115C°
- 5.Soldering temperature range:250C°±10C°/5sec

6.Safety approval:

7.RoHS Compliance

8.Critical dimension:

9.Undimensioned Tolerances:

| | | |
|----------------------|----------------|-------|
| Dim.L=(P-1)X3.81+5.0 | Dim B | Dim L |
| Dim.B=(P-1)X3.81 | 0-30mm | ±0.15 |
| P = number of poles | over 30mm-60mm | ±0.20 |
| | over 60mm-90mm | ±0.25 |
| | over 90mm | ±0.30 |
| | | ±0.40 |

HABV381 xx x xxx

- ① Poles 02-24
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue.....
- ③ Custom
- 000 K MARK 00K KUNACON MARK.....

| | | | | | | | | |
|----------------------------------|--------------|--------------|------------|----------|----------------------------|-------|--------|-----------|
| 2 | PIN | BRASS | TIN PLATED | P | | | | |
| 1 | BODY | PA66 UL94V-0 | | 1 | | | | |
| ITEM NAME OF PART MATERIAL NOTES | | | | | | | | |
| DWG | WF. Zhang | DATE | 2016.03.10 | UNITS | MM | SHEET | 1 OF 1 | Tolerance |
| CHK. | WF. Zhang | DATE | 2016.03.10 | SCALE: | NONE 4:1 (:) | REV.: | A | ±0.50 |
| APP. | Marvin Zhang | DATE | 2016.03.31 | TITLE: | HA-BV381 Series Close type | | | ±0.30 |
| | | | | | Vertical(180D) | | | ±0.10 |
| | | | | PART NO. | HABV381xxxxxx | | | X° |
| | | | | DWG NO. | HA-B381-B001 | | | X° |

| | | | | |
|---|------|-------------|------|------|
| △ | SIGN | DESCRIPTION | CHK. | DATE |
| | | | | |



KUNA Contact Technology Co. Ltd
http://www.kunacon.com