



Technical data

1. Nominal voltage: 300V/8A (IEC 160V/8A)  
PITCH: 3.5mm
2. Insulation Withstands Voltage:  
AC1600V/MIN / AC 2500V/MIN
3. Insulation Resistance:  
1000M $\Omega$  or more at DC500V
4. Using temperature range: -40C $^{\circ}$  ~ 115C $^{\circ}$
5. Soldering temperature range: 250C $^{\circ}$   $\pm$  10C $^{\circ}$  / 5sec
6. Safety approval:
7. RoHS Compliance
8. Critical dimension:
9. Undimensioned Tolerances:

	Dim B	Dim L
0-30mm	$\pm 0.15$	$\pm 0.20$
over 30mm-60mm	$\pm 0.20$	$\pm 0.25$
over 60mm-90mm	$\pm 0.25$	$\pm 0.30$
over 90mm	$\pm 0.30$	$\pm 0.40$

HACV350 xx x xxx

- ① Poles 02-24
- ② Color  
0 Black 3 Orange 5 Green 6 Blue.....
- ③ Custom  
000 K MARK 00K KUNACON MARK.....

ITEM	NAME OF PART	MATERIAL	NOTES	QTY
3	FLANGE NUT	BRASS		2
2	PIN	BRASS	TIN PLATED	P
1	BODY	PA66 UL94V-0		1

  

DWG	W/F	DATE	UNITS	SHEET	1 OF 1	Tolerance
CHK.	W/F	DATE	SCALE:	NONE 4:1 ( : )	REV: A	X.X X.X X.XX $\pm 0.10$
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-CV350 Series W/F type Vertical(180D)	X $^{\circ}$ X $^{\circ}$ $\pm 1^{\circ}$

  

PART NO.	DWG NO.	DESCRIPTION	SIGN	CHK.	DATE
HACV350xxxxxx	HA-C350-B001				

KUNA Contact Technology Co. Ltd  
<http://www.kunacon.com>