



Technical data

- 1.Nominal voltage: 150V/8A
PITCH:3.5mm
 - 2.Insulation Withstands Voltage:
AC 1300V/MIN
 - 3.Insulation Resistance:
1000MΩ or more at DC500V
 - 4.Flange tightening torque:
3.0kgf.cm (0.3Nm)
 - 5.Flange screw thread: M2.5
 - 6.Using temperature range:-40C ~+115C°
 - 7.Undimensioned Tolerances:
- | | | |
|----------------|-------|-------|
| 0-30mm | ±0.15 | ±0.20 |
| over 30mm-60mm | ±0.20 | ±0.25 |
| over 60mm-90mm | ±0.25 | ±0.30 |
| over 90mm | ±0.30 | ±0.40 |
- 8.Safety approval:
 - 9.RoHS Compliance
 - 10.Critical dimension:

HFCH350 XX X XXX
 ① Poles 04-4(12x02-2x24)
 ② Color
 0 Black 3 Orange 5 Green 6 Blue G Pale Gray....
 ③ Custom
 000 K MARK 00K KUINACON MARK....

4	Screw nut	BRASS							4
3	PIN 2	COPPER							1/2P
2	PIN 1	COPPER							1/2P
1	BODY	PA66 UL94V-0							1
ITEM NAME OF PART		MATERIAL		NOTES					
DWG	WF. Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance	
CHK.	WF. Zhang	DATE	2016.03.10	SCALE:	NONE 2.5:1 (.)	REV.:	A	±0.50	
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HF-CH350 Series W/flange			±0.30	
				TITLE:	type Right angle (90D)			±0.10	
				PART NO.:	HFCH350XXXXXX			±1°	
				DWG NO.:	HF-C350-B001				

△		
SIGN	DESCRIPTION	DATE
CHK.		

KUNNA Contact Technology Co. Ltd
<http://www.kunnacon.com>