



Technical data

- 1.Nominal voltage: 150V/8A  
PITCH:3.5mm
- 2.Insulation Withstands Voltage:  
AC 1300V/MIN
- 3.Insulation Resistance:  
1000MΩ or more at DC500V
- 4.Flange tightening torque:  
3.0kgf.cm (0.3Nm)
- 5.Flange screw thread: M2.5
- 6.Using temperature range:-40C ~+115C°
- 7.Undimensioned Tolerances:

0-30mm	Dim B	±0.15	Dim L	±0.20
over 30mm-60mm		±0.20		±0.25
over 60mm-90mm		±0.25		±0.30
over 90mm		±0.30		±0.40

- 8.Safety approval:
- 9.RoHS Compliance
- 10.Critical dimension:

HFCV350 xx x xxx  
 ① Poles 04-48(2\*02-2\*24)  
 ② Color  
 0 Black 3 Orange 5 Green 6 Blue G Pale Gray...  
 ③ Custom  
 000 K MARK 00K KUNACON MARK.....

3	Screw nut	BRASS			4
2	PIN	COPPER			P
1	BODY	PA66 UL94V-0			1
ITEM NAME OF PART		MATERIAL		NOTES	
DWG	WF: Zhang	DATE	2016.03.10	UNITS:	MM
CHK.	WF: Zhang	DATE	2016.03.10	SCALE:	NONE 2.5:1 (.)
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HFCV350 Series W/flange type Vertical (180D)
PART NO.		HFCV350xxxxxx		Tolerance	
DWG NO.		HF-C350-B002		±0.50 ±0.30 ±0.10 ±1°	

△		
SIGN	DESCRIPTION	DATE
CHK.		

KUNA Contact Technology Co. Ltd  
<http://www.kunacon.com>