



Technical data

- 1.Nominal voltage: 150V/8A
- PITCH:3.81mm
- 2.Insulation Withstands Voltage: AC 1300V/MIN
- 3.Insulation Resistance: 1000MΩ or more at DC500V

- 4.Using temperature range:-40C~+115C
- 5.Undimensioned Tolerances:

0-30mm over 30mm-60mm over 60mm-90mm over 90mm	Dim B	Dim L
	±0.15 ±0.20 ±0.25 ±0.30	±0.20 ±0.30 ±0.40

- 6.Safety approval:
- 7.RoHS Compliance
- 8.Critical dimension:

- HFDV381 xxx xxx
- ① Poles 04-4(812x02-2x24)
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue G Pale gray.....
- ③ Custom
- 000 K MARK 00K KUNACON MARK.....

2	PIN	COPPER	TIN PLATED	P
1	BODY	PA66 UL94V-0	ALL COLOR	1
MATERIAL				
DWG. W/F. Zhang	DATE 2016.03.10	MM	SHEET: 1 OF 1	Tolerance
CHK. W/F. Zhang	DATE 2016.03.10	SCALE: NONE 2.5:1 (.)	REV.: A	±0.50
APP. Marvin Zhang	DATE 2016.03.31	TITLE: HF-DV381 Series with engagement nose type 180D		±0.30
		PART NO. HFDV381xxxxxx		±0.10
		DWG NO. HF-D381-B002		±1°
SIGNATURE				
DESCRIPTION				
CHK.				
DATE				
KUNA Contact Technology Co. Ltd <a href="http://www.kunacon.com">http://www.kunacon.com</a>				